

The PDK Red Locksets brings heightened security and convenience to any PDK.io 2.0 system. PDK's Red Locksets come in a cylindrical and a deadbolt variety, allowing for the ultimate flexibility in your installs.

Models

Cylindrical Lock (Satin Chrome): **RLC2PKS**

Cylindrical Lock (Black): **RLC2PKB**

Deadbolt Lock (Satin Chrome): **RLDBPKS**

Deadbolt Lock (Black): **RLDBPKB**



Specifications

Communication

HubNet (2.4 GHz/ 802.15.4)

Wireless Range: 100ft

Environmental

Temperature: -20° ~ +65° C / -4° ~ +149° F

Humidity: 0 - 95% relative humidity non-condensing

Protection Rating: Cylindrical IP65 (exterior/interior)

Protection Rating: Deadbolt IP65 (exterior side)

Compliance

FCC Part 15 

ADA Compliance 

Conforms to UL 10C 

ANSI/BHMA Grade 2

TAA Compliant

 wirelesslock

For custom lockset orders
use our SKU Builder:



Manufacturer's Limited Warranty

One to five-year warranty against defects in materials and workmanship. For full details, visit www.prodatakey.com/warranty

Visit www.prodatakey.com/resources to access marketing, installation, and support resources.
For questions about the PDK Red Wireless Lockset, please contact support@prodatakey.com.

deadboltlocksets

access control credentials



mobile



prox



pin



key

Features

- Built from PDK's Heavy Duty Deadbolt
- Designed for quick installation
- 4 AA Alkaline batteries last up to 2 years or 5V DC
- Able to schedule specific access windows
- Log and track access events and status
- Monitors and protects openings with door obstruction alerts
- Battery status and low battery alerts

specifications

Door Thickness	1-3/8" to 1-3/4"
Backset	1-3/8" to 1-3/4" 2-3/8" - 2-3/4" (Adjustable)
Credentials	• RFID • Smartphone • PIN • Mechanical Key
Keyways	• Conventional • SFIC • High Security • UL437
Credential Compatibilities	• Prox (Optional) • MIFARE DESFire EV1/EV2/EV3/Light • MIFARE Ultralight EV1/AES • MIFARE Classic
Communication	• BLE 4.2 • BLE 5.2
Batteries Required	4 AA Alkaline Batteries
Operating Temperatures	-20C to 65C • 0-95% Humidity (Non-Condensing)
Certification & Compliances	• FCC Part 15 • UL/cUL 10C 20-Minutes
Modes	• Complies with ADA (Americans with Disabilities Act) • Standalone • Online
Finishes	• 606 (US4) • 613E • 622 (US19) • 626 (US26D)
Warranty	Two (2) year Mechanical / Two (2) year Electronics
Country of Origin	Assembled in USA




exterior view




interior view

cylinders



architectural finishes



606 (US4)
Satin Brass

613E
Dark Oxidized Satin
Bronze (Equivalent)

622 (US19)
Flat Black

626 (US26D)
Satin Chromium



cylindricallocksets

access control credentials



mobile



prox



pin



key

Features

- Built from PDK's Grade 2 Cylindrical Lock
- Designed for quick installation
- 4 AA Alkaline batteries last up to 2 years or 5V DC
- Able to schedule specific access windows
- Log and track access events and status
- Enable auto lock/unlock for enhanced security
- Battery status and low battery alerts



exterior view

cylinders



levers



PHILADELPHIA – PHL



BOSTON – BSN



MIAMI – MIA



ORLANDO – ORL

specifications

Door Thickness	1-3/8" to 1-3/4"
Backset	• 2-3/8" • 2-3/4" (Standard) • 5"
Credentials	• RFID • Smartphone • PIN • Mechanical Key
Keyways	• Conventional • SFIC • High Security • UL437
Credential Compatibilities	• Prox (Optional) • MIFARE DESFire EV1/EV2/EV3/Light • MIFARE Ultralight EV1/AES • MIFARE Classic
Communication	• BLE 4.2 • BLE 5.2
Batteries Required	4 AA Alkaline Batteries
Operating Temperatures	-20C to 65C • 0-95% Humidity (Non-Condensing)
Certification & Compliances	• FCC Part 15 • UL/cUL 10C 20-Minutes
Modes	• Complies with ADA (Americans with Disabilities Act) • Standalone • Online
Finishes	• 606 (US4) • 613E • 622 (US19) • 626 (US26D)
Warranty	Two (2) year Mechanical / Two (2) year Electronics
Country of Origin	Assembled in USA

architectural finishes



606 (US4)
Satin Brass



613E
Dark Oxidized Satin
Bronze (Equivalent)



622 (US19)
Flat Black



626 (US26D)
Satin Chromium

